



Product Service

# CERTIFICATE

No. Z2 104598 0022 Rev. 00

**Holder of Certificate:** **Mysolar Manufacturing (Shanghai)Co.,Ltd.**  
Room 505-A, Fl 5th, No.507, Wuning Rd, Putuo District  
200063 Shanghai  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:** **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**Mono-Crystalline Silicon Photovoltaic Module**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 701262402602-00

**Valid until:** 2029-04-15

**Date,** 2024-05-29

( Zhulin Zhang )

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

# CERTIFICATE

No. Z2 104598 0022 Rev. 00

## Model(s):

MSxxxN-DHBG,xxx=670 to 710 in steps of 5  
MSxxxN-DHBG,xxx=610 to 645 in steps of 5  
MSxxxN-DHBGA,xxx=585 to 620 in steps of 5  
MSxxxN-DHBGA,xxx=535 to 565 in steps of 5  
MSxxxN-DHBGA,xxx=480 to 505 in steps of 5  
MSxxxN-DHBGA,xxx=425 to 450 in steps of 5  
MSxxxN-DHBAZ,xxx=605 to 640 in steps of 5  
MSxxxN-DHBAZ,xxx=555 to 585 in steps of 5  
MSxxxN-DHBAZ,xxx=505 to 530 in steps of 5  
MSxxxN-DHBAZ,xxx=455 to 480 in steps of 5  
MSxxxN-DHBAY,xxx=585 to 615 in steps of 5  
MSxxxN-DHBAY,xxx=535 to 560 in steps of 5  
MSxxxN-DHBAY,xxx=440 to 460 in steps of 5  
MSxxxN-DHBAX,xxx=565 to 600 in steps of 5  
MSxxxN-DHBAX,xxx=520 to 550 in steps of 5  
MSxxxN-DHBAX,xxx=470 to 500 in steps of 5  
MSxxxN-DHBAX,xxx=425 to 450 in steps of 5  
MSxxxN-DHBA,xxx=600 to 635 in steps of 5  
MSxxxN-DHBA,xxx=555 to 585 in steps of 5  
MSxxxN-DHBA,xxx=515 to 535 in steps of 5  
MSxxxN-DHBA,xxx=465 to 485 in steps of 5  
MSxxxN-DHBA,xxx=415 to 440 in steps of 5  
MSxxxN-DHBA,xxx=370 to 390 in steps of 5  
xxx is standing for rated output power at STC

## Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute No. 10 West Kaifa Road, Yangzhou 225009 Jiangsu, P. R. China
Safety Class:	Class II
Maximum System Voltage:	1500 V DC
Fire Safety Class:	Class C according to UL790

## Tested according to:

IEC 61215-1:2021  
EN IEC 61215-1:2021/AC:2021  
IEC 61215-1-1:2021  
EN IEC 61215-1-1:2021  
IEC 61215-2:2021  
EN IEC 61215-2:2021  
IEC 61730-1:2023  
IEC 61730-2:2023